


## Capacitor, tantalum, 680 uF, 7343, +/-20% Tol, 4V@85C



Cutout at KEMET's option (either end); see note about P and R dimensions and cutout.

## **Dimensions (mm)**

## **Specifications**

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	7.3	+/-0.3	Capacitance:	680 uF
W	4.3	+/-0.3	Voltage DC @ 85C:	4V
н	4	+/-0.3	Voltage DC @ 105C:	3.2V
К	2.3	+/-0.2	Tolerance:	+/-20%
F	2.4	+/-0.1	Application:	Low ESR
S	1.3	+/-0.3	Body Type:	Molded Chip
В	0.5	+/-0.15	Temperature Range:	-55/+105C
Х	0.1	ref	ESR:	10 mOhm
Р	1.7	ref	Footprint:	7343
R	1	0.13	Termination:	Tin
			Leakage Current:	272 uA
			<b>Dissipation Factor:</b>	10%
			Ripple @ 25C:	5.2 A
			Ripple @ 85C:	4.6 A
			Ripple @ 105C:	2.1 A

Package Kind:

Package Quantity:

T&R

400

Notes: -E



© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.